

## FIELD OF APPLICATION

The AMBIENT LED range of luminaires provides indirect lighting. Recommended for the ambient lighting of restrooms in kindergartens and nurseries.



## MATERIAL

**Luminaire body:** epoxy polyester powder painted steel sheet in RAL9003 color.

**Reflector:** steel sheet, powder painted to the same color as the luminaire body.

## FIXING

The luminaire can be mounted into artificial ceilings.

The luminaire can be mounted onto the ceiling with the optional mounting bracket.

warranty <b>5</b> year	<b>LED</b>	<b>230V</b> <b>50Hz</b>	<b>CRI</b> <b>&gt;80</b>	<b>SDCM</b> <b>3</b>	<b>CCT</b> <b>4000K</b>	<b>IP</b> <b>20</b>		<b>Ta</b> <b>25°C</b>	
------------------------------	------------	----------------------------	-----------------------------	-------------------------	----------------------------	------------------------	---	--------------------------	---

Order number	Type	LED Modules luminous flux (lm)	LED Modules efficiency (lm/W)	Luminaire luminous flux (lm)	Luminaire efficiency (lm/W)	LED Modules power (W)	Luminaire power (W)	A (mm)	B (mm)	C (mm)	F (mm)	Weight (kg)
60 182 324 103	AMBIENT LED	6520	191	2650	66	34	40	595	595	100	572	5,7
60 181 000 608	AMBIENT LED MOUNTING BRACKET	-	-	-	-	-	-	600	600	120	-	2,3

Options:

<b>CRI</b> <b>&gt;90</b>	<b>CCT</b> <b>3000K</b>
-----------------------------	----------------------------

